



TTS
Tuinhof Tankcontainer Solutions

TTS
Tuinhof Tankcontainer Solutions

TTS

Tuinhof Tankcontainer Solutions

Product Data Sheet:

Dimensions: 1200x800x1200 (LxWxH)
 Weight: 250 kg
 Power: 230V/50Hz - 16Amp.
 Master tank: 1
 Slave tank: 4
 Total max. capacity: 15.000 ltr
 Standard hose: 10 mtr
 Standard cable: 10 mtr



Parralel Generator Supply SKID (PGSS)

Application:

Flexible fuel supply for your generator, compressor, climate control or any other fuel consumption device. In cases you need a big volume fuel on site and a standard IBC Fuel Tank is not big enough. With the PGSS you can easy up-scale or down scale your capacity needs with standard IBC's.

Design:

The PGSS is designed to connect 5 standard IBC's. The consumer is connected to the so-called master tank and the 4 other tanks are the so-called slave tanks. The PGSS is controlling the master tank as well as the slave tanks.

The master tank is leading. If a certain level is reached, the pumps on the PGSS will start and fill the master tank. The control unit on the PGSS controls the level in all tanks. All safeties on are double executed (electrical and mechanical).

The system is flexible and all standard IBC's sizes and brands can be used. This means you can connect 1, 2, 3 and/or 4 slave tanks on 1 master tank.



K.v.K. 62593927
 BTW NL138189146B01